



Available online at www.sciencedirect.com



Brain and Cognition xxx (2005) xxx-xxx

**Brain  
and  
Cognition**

www.elsevier.com/locate/b&amp;c

# Crowded and sparse domains in object recognition: Consequences for categorization and naming

Tim M. Gale<sup>a,b,c,\*</sup>, Keith R. Laws<sup>c</sup>, Kerry Foley<sup>a</sup>

<sup>a</sup> Department of Psychiatry, QEII Hospital, Welwyn Garden City, UK

<sup>b</sup> School of Computer Science, University of Hertfordshire, Hatfield, UK

<sup>c</sup> School of Psychology, University of Hertfordshire, Hatfield, UK

Accepted 24 October 2005

## Abstract

Some models of object recognition propose that items from structurally crowded categories (e.g., living things) permit faster access to superordinate semantic information than structurally dissimilar categories (e.g., nonliving things), but slower access to individual object information when naming items. We present four experiments that utilize the same matched stimuli: two examine superordinate categorization and two examine picture naming. Experiments 1 and 2 required participants to sort pictures into their appropriate superordinate categories and both revealed faster categorization for living than nonliving things. Nonetheless, the living thing superiority disappeared when the atypical categories of body parts and musical instruments were excluded. Experiment 3 examined naming latency and found no difference between living and nonliving things. This finding was replicated in Experiment 4 where the same items were presented in different formats (e.g., color and line-drawn versions). Taken as a whole, these experiments show that the ease with which people categorize items maps strongly onto the ease with which they name them.

© 2005 Published by Elsevier Inc.

**Keywords:** Category-specific; Visual crowding; Perceptual differentiation; Picture naming; Picture categorization

## 1. Introduction

Understanding and interpreting category-specific impairments in patients relies upon knowing how a neurologically intact population performs on the same kinds of task; and this has, until relatively recently, been neglected in most accounts of category specificity (see Laws, *in press*; Laws, Gale, Leeson, & Crawford, 2005). Given the greater frequency of living thing impairments reported to date it has often been assumed that normal controls should be less accurate and slower to name items from living thing categories. Indeed, some studies have described this pattern and the explanation given is that living things share greater intra-category structural similarity relative to nonliving

things (Gaffan & Heywood, 1993; Humphreys, Riddoch, & Quinlan, 1988; Lloyd-Jones & Humphreys, 1997a, 1997b).

Some models of object recognition assume that competition between structural descriptions gives rise to processing advantages for certain classes of stimuli (Gerlach, 2001; Humphreys & Forde, 2001; Humphreys et al., 1988; Tranel, Logan, Frank, & Damasio, 1997). Furthermore, models such as the Cascade (Humphreys et al., 1988) and Hierarchical Interactive Theory (HIT: Humphreys & Forde, 2001) propose that the direction of category advantage depends upon the level of processing required by a task. For example, if a target item shares a similar structural description to several within-category associates, it will take longer to resolve a specific 'structural' representation than if the target item is structurally distinctive. This will affect the activation of item-specific semantic and phonological representations such that a significant delay in object naming should be measurable. But, by contrast, greater competition for some categories (e.g., living things) at the level of

\* Corresponding author. Fax: +44 0 1707 365169.

E-mail address: t.gale@herts.ac.uk (T.M. Gale).

structural representation should produce a processing advantage on tasks where exactly the same stimuli require superordinate category recognition. Presumably, if living things are characterized by greater structural similarity, those visual properties that are common to superordinate category members should be readily available and therefore promote easier superordinate categorization for this class of items. By contrast, the very same properties that coherently unite items from living thing superordinates will make them more difficult to discriminate at the item level.

Few studies have compared superordinate categorization between living and nonliving things, and the evidence in favor of the proposals outlined above is somewhat equivocal (Lloyd-Jones & Humphreys, 1997b; Price & Humphreys, 1989). Notably, one reports faster naming and classification for living (structurally similar) things (Lloyd-Jones & Humphreys, 1997b); while the other reports no difference for naming, but a living advantage for classification (Price & Humphreys, 1989). Furthermore, Price and Humphreys (1989) did not systematically control for variables such as word frequency, visual complexity, and concept familiarity (all of which are known to disadvantage the naming of living things). Lloyd-Jones and Humphreys (1997b) co-varied these nuisance variables, but they examined a very restricted range of items, e.g., fruit and vegetables versus clothing and furniture. More recent studies have shown that when the above named variables are matched across category, normal subjects tend to be more accurate and faster to name living things (Brousseau & Buchanan, 2004; Laws, 1999, 2000; Laws & Gale, 2002; Laws, Leeson, & Gale, 2002; Laws & Neve, 1999; McKenna & Parry, 1994). Hence, the data on these issues remain uncertain.

Another important issue concerns the treatment of categories that appear to elicit counter-intuitive response profiles in patients. Many studies have noted that musical instruments tend to associate with living things while body parts seem to behave more like nonliving things (Barbarotto, Capitani, & Laiacina, 2001; Laws, Gale, Frank, & Davey, 2002; Parkin & Stewart, 1993). It is therefore important to examine the contribution of these categories to any emergent category effects. In this paper, we present four experiments which examine superordinate categorization and picture naming using the same sets of stimuli across each task. If living things are more visually crowded, we should predict a double dissociation in categories across tasks.

## 2. Experiment 1

### 2.1. Method

#### 2.1.1. Participants

Fifty participants were recruited (25 male, 25 female) with a mean age of 33 ( $\pm 14$ ) years. All had normal or corrected-to-normal vision, none had cognitive or perceptual impairments, and all spoke English as their first language. The group comprised hospital administrative and cleaning staff, nurses and students.

#### 2.1.2. Materials

We used 100 picture cards depicting items from 10 different superordinate categories. There were five living thing categories (animals, birds, body parts, fruit, and vegetables) and five nonliving thing categories (clothing, furniture, musical items, tools, and vehicles), with 10 different items per category. The pictures were grey scale versions of the Snodgrass and Vanderwart (1980) corpus adapted by Rossion and Pourtois (2004). These pictures use the same line detail as the original corpus, but also include grey scale shading and some textural detail, thereby providing representations that are more realistic. The pictures were presented on laminated cards of 10 cm<sup>2</sup>. A full list of items appears in Appendix A.

Living and nonliving things were matched for, familiarity ( $3.24 \pm 1.01$  vs.  $3.53 \pm 0.87$ ,  $F[1, 98] = 2.41$ ,  $p > .1$ ), visual complexity ( $3.01 \pm 0.93$  vs.  $3.03 \pm 0.85$ ,  $F[1, 98] < 1$ ,  $p > .9$ ) from Snodgrass and Vanderwart (1980), and log word frequency ( $1.11 \pm 0.64$  vs.  $1.13 \pm 0.75$ ,  $F[1, 98] < 1$ ,  $p = .88$ ; from Kuçera & Francis, 1967).

#### 2.1.3. Procedure

The picture cards were divided into two randomly shuffled sets containing the 50 living and the 50 nonliving things. The aim of the task was to sort each pack into its five superordinate categories as quickly as possible. This was done by placing the cards underneath 5 large category labels (e.g., “animals,” “fruit,” etc.). The first pack of 50 cards was laid facedown in front of the participant who then turned one card over at a time and allocated it to the appropriate category label. If a card was accidentally allocated to the wrong category, the participant was allowed to correct the mistake. The time required to complete the task (i.e., to sort all 50 cards into their appropriate categories) was recorded by stopwatch from the moment that the first card was turned over to the time at which the last card was allocated. Each participant sorted both packs of cards but the task order (L, NL vs. NL, L) was randomly determined for each participant.

## 2.2. Results and summary

### 2.2.1. Errors and outliers

The number of sorting errors was low (the means for living and nonliving things were 2.44 and 2.48%, respectively,  $F[1, 49] < 1$ ,  $p > .9$ ). The breakdown of errors by superordinate category was as follows: birds (6.4%), vegetables (5.4%), furniture (5%), vehicles (4.8%), musical items (2%), tools (0.6%), fruit (0.4%), clothing (0%), body parts (0%), and animals (0%). Sorting times exceeding two standard deviations above or below the mean were removed (this resulted in two being removed for living things and three for nonliving things).

### 2.2.2. Category differences

Living things were sorted into their five superordinate categories significantly faster than nonliving things ( $94.9 \pm 17.8$  vs.  $101.5 \pm 15.5$ :  $F[1, 93] = 13.06$ ,  $p < .001$ ).

160 This finding accords with the notion that greater visual  
161 crowding facilitates the identification of living than nonliv-  
162 ing thing category members. The task used in Experiment 1  
163 does not, however, address the question of whether any rel-  
164 ative difficulty exists across the 10 categories. For example,  
165 do some superordinate categories produce atypical profiles  
166 that might mask or distort the overall living or nonliving  
167 profile? We turn to this in Experiment 2.

### 168 3. Experiment 2

#### 169 3.1. Method

##### 170 3.1.1. Participants

171 Seventy-eight participants were recruited (39 female, 39  
172 male) with a mean age of 36 ( $\pm 12.4$ ) years. All had normal  
173 or corrected-to-normal vision, none had cognitive or per-  
174 ceptual impairments, and all spoke English as their first  
175 language. The group comprised postgraduate engineering  
176 and computing students, department store workers, and  
177 hospital administrative staff.

##### 178 3.1.2. Materials

179 The materials were identical to those described in Exper-  
180 iment 1.

##### 181 3.1.3. Procedure

182 In this experiment, participants selected items belonging  
183 to a target superordinate category from an array of distrac-  
184 tors. Each trial comprised 30 picture cards representing  
185 three superordinate categories (e.g., animals, vegetables,  
186 furniture). These were shuffled and laid out on the desktop  
187 in an array of six columns by five rows. The array was cov-  
188 ered until the participant was ready to begin the trial. The  
189 participant was then given a set of 10 large (3 cm in diame-  
190 ter) identical coins that were numbered consecutively from  
191 1 to 10. The participant was asked to identify all 10 items  
192 belonging to the given target category (e.g., animals) by  
193 placing the coins on the appropriate picture cards within  
194 the array. This method of marking the target cards was  
195 found to be more reliable than either (i) picking the cards  
196 up by hand or (ii) sorting them into target and nontarget  
197 piles. The latter approaches have been used in previous  
198 studies, but may create difficulties for subjects (for example,  
199 if participants have trouble in picking up some of the cards,  
200 or drop them).

201 The time taken to complete the trial was recorded in sec-  
202 onds and milliseconds from the moment the covering was  
203 removed until the last coin had been placed. The order in  
204 which items were identified as target category members for  
205 each trial was recorded by noting the number of the coin  
206 (1–10) that was placed on each picture. Each participant  
207 completed three trials, one after the other [i.e., they saw  
208 three different arrays comprising 90 cards (9 categories) in  
209 total]. None of the individual cards or categories was seen  
210 more than once by any participant. A running order of tar-  
211 get and distractor categories was drawn up in advance to

ensure that each category appeared as a target an equal 212  
number of times across all trials. Moreover, each of the 10 213  
categories appeared as distractors with equal probability. 214  
In each array of 30 cards, the two distractor categories 215  
always comprised one living and one nonliving category. 216

#### 3.2. Results and summary 217

##### 3.2.1. Errors and outliers 218

219 A total of 234 trials were run. Categorization errors,  
220 where a participant placed a coin on a nontarget category  
221 item and did not correct the error, were made in only 15  
222 (6.4%) trials and these were excluded from the latency anal-  
223 yses. These errors were distributed as follows: musical items  
224 (5), birds (4), fruit (2), vegetables (2), and furniture (2). Of  
225 the 219 remaining trials, a further 11 were also excluded  
226 because the latencies exceeded two standard deviations  
227 beyond the mean. These were exclusive cases, where partici-  
228 pants spent a lot of time pondering on whether a specific  
229 item should be included in a category or not (one example  
230 being whether ‘piano’ should be classed as a musical instru-  
231 ment or an item of furniture). All primary analyses were  
232 run with outliers included and excluded. Excluding them  
233 made no difference to the statistical significance of any of  
234 the tests. However, the descriptive and inferential statistics  
235 we report here are based on the smaller dataset of 208 trials  
236 since this represents the total number of trials completed  
237 accurately and without distraction.

##### 3.2.2. Category differences 238

239 The mean time for selecting items from living thing cate-  
240 gories was 12.90 ( $\pm 4.32$ ) s compared with 14.61 ( $\pm 4.60$ ) s  
241 for nonliving things. This difference was reliable  
242 ( $F[1, 206] = 7.62, p < .01$ ). This difference, however, disap-  
243 peared when the categories of body parts and musical  
244 instruments were removed from the analysis (13.49 vs.  
245 13.95:  $F[1, 168] < 1$ ). With body parts removed, the means  
246 for living vs. nonliving were 13.31 ( $\pm 4.7$ ) vs. 14.61 ( $\pm 4.6$ ),  
247  $F[1, 186] = 3.64, p = .06$ . With musical instruments removed,  
248 the means for living vs. nonliving were 12.90 ( $\pm 4.3$ ) vs. 13.89  
249 ( $\pm 4.2$ ),  $F[1, 189] = 2.54, p = .11$ . A breakdown of mean RTs  
250 by superordinate category is displayed in Table 1.

Table 1

Mean and SD latencies for the 10 categories, along with the mean values on background variables (in Experiment 2)

Category	Mean RT [SD]	Familiarity	VC	WF (log)
Animals	10.67 [2.86]	2.63	3.85	1.26
Body parts	11.23 [1.39]	4.67	2.38	1.79
Clothing	11.76 [2.52]	4.11	2.54	1.43
Birds	12.93 [5.21]	2.29	3.43	0.83
Fruit	13.50 [3.61]	3.39	2.31	0.89
Tools	13.71 [4.64]	3.1	2.36	0.71
Furniture	14.88 [3.83]	4.27	2.62	1.45
Vehicle	15.44 [4.82]	3.62	3.73	1.16
Vegetable	16.86 [4.93]	3.22	3.1	0.58
Musical items	17.89 [5.01]	2.56	3.89	0.84

### 3.2.3. Predicting categorization order

The placing of consecutively numbered coins allowed us to calculate a *mean retrieval position* for each of the 10 items in each category. If retrieval order is random, little variation in mean retrieval position among the 10 items should emerge (i.e., the mean position score for each item would approximate 5.5). By contrast, if any systematic factors influenced retrieval order, we should expect considerable variation in mean retrieval position values within each superordinate. Table 2 displays the range of mean retrieval position values for each superordinate.

We examined the association between mean retrieval position and two measures of category typicality (from Battig & Montague, 1969). These measures were: (i) typicality rank, and (ii) the proportion of respondents citing the exemplar as a category member. Both typicality measures significantly correlated with retrieval position ( $r = 0.34$ ,  $F[1, 97] = 14.74$ ,  $p = .0006$ ;  $r = 0.23$ ,  $F[1, 97] = 5.23$ ,  $p < .03$ , respectively). Looking at living and nonliving things separately, typicality rank was a significant predictor of mean retrieval position for nonliving things ( $r = 0.39$ ,  $F[1, 49] = 8.53$ ,  $p = .005$ ), but not for living things ( $r = 0.26$ ,  $F[1, 47] = 3.37$ ,  $p = .07$ ). Proportion of respondents citing exemplar was a significant predictor for nonliving things ( $r = 0.32$ ,  $F[1, 49] = 5.38$ ,  $p = .025$ ), but again not for living things ( $r = 0.12$ ,  $F < 1$ ).

Experiment 2 confirms the faster superordinate categorization for living things; however, it also reveals that the dissociation does not sustain when musical instruments and body parts are excluded (both of which would favor the advantage for living things because they are processed relatively quickly and slowly, respectively). The order in which category members were identified varied according to item prototypicality and is consistent with the notion that participants selected items on their 'goodness of fit' to a category name rather than necessarily identifying them. Furthermore, mean retrieval positions correlated with typicality for nonliving things, but not for living things. This pattern accords with that reported by Riddoch and Humphreys (1987), who argued that the correlation for structurally distinct items (nonliving) reflects the fact that

typical nonliving things are classified more quickly than atypical nonliving things; however, typicality makes no difference for living things. In other words, typicality determines the time taken to access semantic information for nonliving, but not living things. For living things, it may be that categorization is determined more by structural information than semantic (typicality) information. In Experiment 3, we investigate object naming using exactly the same stimuli and examine whether the reverse dissociation is observed (i.e., a significant advantage for nonliving things).

## 4. Experiment 3

### 4.1. Method

#### 4.1.1. Participants

Twenty undergraduate students (9 females, 11 males) of mean age 26 years (range 19–43) viewed all 100 pictures in a naming latency task. All had normal, or corrected-to-normal, vision and spoke English as their first language.

#### 4.1.2. Materials

The same 100 grey scale pictures used in Experiment 1 were presented digitally.

#### 4.1.3. Procedure

The stimuli were presented against a white background on a high-resolution monitor using SuperLab software run on an Apple Macintosh computer. Each drawing extended maximum dimensions of  $9.91 \times 6.95$  cm ( $281 \times 197$  pixels) and was viewed from a distance of 50 cm. There was no time limit for responding. Participants were asked to name each item as it appeared on the screen and the latency of their response was recorded using a voice key. A blank white screen appeared between each presented picture for 1000 ms. Pictures were presented randomly and timing accuracy was to within one thousandth of a second. Before collating the raw latency data, any score that was three or more standard deviations beyond an individual participant's mean score were excluded, as was the latency for any item that was named incorrectly.

### 4.2. Results and summary

The naming error rate was very low (0.3% of all responses) so we did not analyze errors. Three items generated mean latencies that exceeded two standard deviations beyond the pooled mean (i.e., they exceeded a cut-off score  $\geq 1433$  ms in these data). These items were: artichoke (1621 ms), asparagus (1617 ms), and French horn (1634 ms). Excluding these outlying items made no difference to the living vs. nonliving comparison. Comparison of naming latencies for living and nonliving things ( $1022 \pm 158$  ms vs.  $1062 \pm 162$  ms) revealed no significant difference ( $F[1, 98] = 1.46$ ,  $p = .23$ ). Removing body parts and/or musical instruments made no difference to the results ( $F < 1$ ).

Table 2

The range of mean retrieval positions for items in the 10 superordinates

Category	Range of mean retrieval position across 10 exemplars	Most common first selection	Most common last selection
Animals	4.04–6.17	Cow	Goat
Body Parts	4.86–6.52	Toe	Arm
Clothing	4.09–7.00	Sweater	Shoe
Birds	4.23–6.73	Rooster	Peacock
Fruit	4.09–7.36	Strawberry	Banana
Tools	3.96–7.23	Wrench	Paintbrush
Furniture	4.10–7.70	Table	Television
Vehicle	4.14–6.76	Bicycle	Sailboat
Vegetable	3.82–7.00	Celery	Mushroom
Music	4.32–6.82	Guitar	Accordion

A larger range is indicative of greater systematicity in item retrieval order (in Experiment 2).

#### 4.2.1. Relationship between naming latency and superordinate categorization latency

The mean naming latencies from Table 3 correlated significantly with the mean superordinate categorization latencies in Table 1 ( $r = 0.84$ ,  $F[1,9] = 18.6$ ,  $p < .003$ ). Animals, body parts and clothing, the three categories with the quickest superordinate categorization times, were also the fastest named categories. Similarly, musical instruments and vegetables elicited the two slowest latencies on both the superordinate categorization and item naming tasks.

If the apparent advantages for living thing categorization in Experiments 1 and 2 reflect greater visual overlap for living things, we would have expected the reverse dissociation on the same set of stimuli in Experiment 3; however, no significant difference emerged in the naming latencies for living and nonliving things.

### 5. Experiment 4

Given the null finding in Experiment 3, we tested a new group of participants on the same 100 items, but this time depicted: as black and white line drawings (as per the original Snodgrass and Vanderwart corpus); and as color drawings (also recently adapted and published by Rossion & Pourtois, 2004).

#### 5.1. Method

##### 5.1.1. Participants

Thirty undergraduate students (18 females, 12 males) of mean age 25 years (range 18–48) viewed the monochrome and color pictures. All participants had normal, or corrected-to-normal, vision and spoke English as their first language.

##### 5.1.2. Materials

The same 100 items used in Experiments 1–3 were presented digitally as (i) monochrome line drawings and (ii) color versions for a naming latency task.

##### 5.1.3. Procedure

The procedure was identical to that of Experiment 3.

Table 3  
Mean picture-naming latencies by superordinate category (in Experiment 3)

Category	Mean naming RT	Range (means)	Fastest named	Slowest named
Body parts	899	761–1044	Eye	Finger
Animals	1010	784–1114	Dog	Cow
Clothing	1028	732–1381	Sock	Coat
Vehicle	1042	825–1415	Airplane	Wagon
Tools	1048	826–1281	Saw	Pliers
Birds	1068	781–1359	Owl	Chicken
Fruit	1072	887–1269	Pear	Orange
Furniture	1079	899–1421	Television	Desk
Musical items	1167	885–1634	Bell	French horn
Vegetables	1189	821–1621	Carrot	Artichoke

#### 5.2. Results summary

- (i) Monochrome drawings (BW): living and nonliving things ( $978 \pm 172$  ms vs.  $1017 \pm 142$  ms) revealed no significant difference in naming latency ( $F[1,98] = 1.54$ ,  $p = .22$ ). Removing body parts and/or musical instruments from the analysis made no difference to the results ( $F < 1$ ). Naming errors constituted less than 1% of total responses and were not analyzed.
- (ii) Color pictures: living and nonliving things ( $945 \pm 165$  ms vs.  $953 \pm 178$  ms) again failed to reveal any significant difference ( $F[1,98] < 1$ ). Removing body parts and/or musical instruments from the analysis made no difference to the results ( $F < 1$ ). Again, the naming error rate was less than 1%.

Experiment 4 again did not find the predicted advantage for nonliving naming. These results confirmed those of Experiment 3, and extended the findings to three variants of the same stimuli using different participant groups.

### 6. Discussion

As far as we are aware, these experiments are the first to directly compare categorization and naming across category on the same set of matched stimuli from a broad range of categories. In this respect, this study directly examines hypotheses derived from models that emphasize a role for visual crowding (e.g., in particular, the notion that high structural similarity gives rise to more efficient access to super-ordinate semantic information and slowed access to information about individual objects).

In Experiments 1 and 2, participants selected items belonging to a target superordinate from an array of distractor items and were significantly faster to categorize items within living thing superordinates. Although this pattern is consistent with the assumptions and predictions of visual crowding models, the latency difference disappeared when the atypical living and nonliving categories of body parts and musical instruments were excluded (Experiment 2). Additionally, Experiments 3 and 4 failed to reveal a picture naming advantage in favor of nonliving things (as predicted by visual crowding models). Again, body parts and musical instruments were among the fastest and slowest, respectively, to be named. Hence, the treatment of these two superordinates may play a critical role in determining the outcomes of category-specific studies.

The proposal that naming should be faster for nonliving (structurally dissimilar) than living (structurally similar) things failed to receive any support from the current study, with no difference emerging on the purportedly more sensitive task of picture naming (i.e., where more specific and uniquely identifying information is required). Of course, with null results it is possible that the study did not have sufficient power to detect a true difference. We calculated the 95% confidence intervals for the living-nonliving effect size for naming grey scale, monochrome and color images

431 ( $d=0.24$ ,  $CI=-0.15$  to  $0.63$ ;  $d=0.25$ ,  $CI=-0.15$  to  $0.64$ ;  
 432  $d=0.14$ ,  $CI=-0.25$  to  $0.53$ , respectively).<sup>1</sup> As expected  
 433 from the nonsignificant results on all stimulus sets, the con-  
 434 fidence intervals span through zero. In each case, the effect  
 435 size is small and is in the direction of an advantage for nam-  
 436 ing living things (which runs contrary to the position of  
 437 some authors). Looking at the confidence intervals for the  
 438 effect sizes, it is clear that at best, the effect size in favor of  
 439 faster naming of nonliving relative to living things is likely  
 440 to be very small ( $-0.15$ ,  $-0.15$ , and  $-0.25$ ). The replication  
 441 of a null result using three varieties of the same items leads  
 442 us to believe that this is a genuine finding; and cannot be  
 443 attributed to confounds such as familiarity, visual complex-  
 444 ity, name frequency or age-of-acquisition. Leaving aside the  
 445 lack of evidence for nonliving naming, we also need to con-  
 446 sider why the data presented here also fail to accord with  
 447 studies that report a living advantage (Brousseau &  
 448 Buchanan, 2004; Laws, 1999, 2000; Laws & Gale, 2002;  
 449 Laws et al., 2002; Laws & Neve, 1999; McKenna & Parry,  
 450 1994). One possibility is that, under normal viewing condi-  
 451 tions, any effect size is small for picture naming and that  
 452 small changes in stimuli or presentation and response con-  
 453 ditions may affect the living advantage. Recent studies with  
 454 normal healthy subjects seem to support the latter notion  
 455 (Gerlach, 2001; Låg, in press). Nonetheless, the direction of  
 456 the findings in Experiments 3 and 4 were always in the  
 457 opposite direction to that predicted by visual crowding  
 458 hypotheses (i.e., living things were named slightly faster).  
 459 Whatever the reason for the living advantage appearing or  
 460 disappearing in some studies, little evidence supports a non-  
 461 living naming advantage when matched stimuli are pre-  
 462 sented in normal viewing conditions.

463 The data presented in this paper suggest several things.  
 464 First, explanations for category specific deficits must  
 465 address naming and categorization performance for atyp-  
 466 ical categories. Second, that within the context of atypical  
 467 categories, the profile seen in patients is mirrored by that  
 468 found in neurologically intact individuals and so may be an  
 469 exaggeration of the normal profile (i.e., body parts being  
 470 relatively preserved and musical instruments being poorly  
 471 recognized and named). Finally, although the structural  
 472 similarity hypothesis suggests that superordinate picture  
 473 classification and picture naming should provide inverse  
 474 profiles, our categorization and naming experiments show  
 475 that the ease with which people classify items maps strongly  
 476 onto the ease with which they name them, i.e., the same cat-  
 477 egories that are difficult or easy to classify are difficult/easy  
 478 to name.

<sup>1</sup> To address the possibility raised by one reviewer, that subjects were producing low error rates at the cost of generally slowed latencies (at a ceiling), we compared just the fastest 50% of living and nonliving latencies for the three picture sets. Each was matched for familiarity, name frequency and visual complexity across category. No significant differences emerged for category and in each case living things were again named more quickly.

## Acknowledgments

479

We thank Prof. Glyn Humphreys, Prof. Henri Cohen,  
 and an anonymous reviewer for their helpful comments on  
 earlier drafts of this paper. We are also very grateful to Ver-  
 ity Leeson for her assistance in collecting naming latency  
 data.

480  
481  
482  
483  
484

## Appendix A. List of items used in all experiments

485

486

*ANIMAL*  
 BEAR  
 COW  
 DOG  
 ELEPHANT  
 GIRAFFE  
 GOAT  
 HORSE  
 LION  
 SHEEP  
 SQUIRREL

*BIRD*  
 CHICKEN  
 DUCK  
 EAGLE  
 OSTRICH  
 OWL  
 PEACOCK  
 PENGUIN  
 ROOSTER  
 SWAN

*BODY PART*  
 ARM  
 EAR  
 EYE  
 FINGER  
 FOOT  
 HAND  
 LEG  
 LIPS  
 NOSE  
 TOE

*CLOTHING*  
 COAT  
 DRESS  
 HAT  
 JACKET  
 PANTS  
 SHIRT  
 SHOE  
 SKIRT  
 SOCK  
 SWEATER

*FRUIT*  
 APPLE  
 BANANA  
 CHERRY  
 GRAPES  
 LEMON  
 ORANGE  
 PEACH  
 PEAR

PINEAPPLE  
STRAWBERRY

FURNITURE

BED  
CHAIR  
COUCH  
DESK  
DRESSER  
REFRIDGERATOR  
ROCKING CHAIR  
STOOL  
TABLE  
TELEVISION

MUSICAL INSTRUMENT

ACCORDIAN  
BELL  
DRUM  
FLUTE  
FRENCH HORN  
GUITAR  
HARP  
PIANO  
TRUMPET  
VIOLIN

TOOL

AXE  
CHISEL  
HAMMER  
PAINTBRUSH  
PLIERS  
RULER  
SAW  
SCISSORS  
SCREWDRIVER  
WRENCH

VEGETABLE

ARTICHOKE  
ASPARAGUS  
CARROT  
CELERY  
LETTUCE  
MUSHROOM  
ONION  
PEPPER  
POTATO  
PUMPKIN

VEHICLE

AEROPLANE  
BIKE  
BUS  
CAR  
HELICOPTER  
MOTORBIKE  
SAILBOAT  
TRAIN  
TRUCK  
WAGON

- Battig, W. F., & Montague, W. E. (1969). Category norms for verbal items in 56 categories: A replication and extension of the Connecticut category norms. *Journal of Experimental Psychology*, *80*, 1–146. 490–492
- Brousseau, G., & Buchanan, L. (2004). Semantic category effect and emotional valence in female university students. *Brain and Language*, *90*, 241–248. 493–495
- Gaffan, D., & Heywood, C. A. (1993). A spurious category-specific visual agnosia for living things in normal human and non-human primates. *Journal of Cognitive Neuroscience*, *5*, 118–128. 496–498
- Gerlach, C. (2001). Structural similarity causes different category effects depending on task characteristics. *Neuropsychologia*, *39*, 895–900. 499–500
- Humphreys, G. W., & Forde, E. M. E. (2001). Hierarchies, similarity and interactivity in object recognition: On the multiplicity of ‘category-specific’ deficits in neuropsychological populations. *Behavioral and Brain Sciences*, *24*, 453–509. 501–503
- Humphreys, G. W., Riddoch, J., & Quinlan, P. T. (1988). Cascade processes in picture identification. *Cognitive Neuropsychology*, *5*, 67–103. 504–506
- Kučera, H., & Francis, W. (1967). *Computational analysis of present-day American English Providence*. Rhode Island: Brown University Press. 507–508
- Låg, T. (in press). Category-specific effects in object identification: What is ‘normal’? *Cortex*. 509–510
- Laws, K. R. (1999). Gender affects naming latencies for living and nonliving things: Implications for familiarity. *Cortex*, *35*, 729–733. 511–512
- Laws, K. R. (2000). Category-specific naming errors in normal subjects: the influence of evolution and experience. *Brain and Language*, *75*, 123–133. 513–515
- Laws, K. R. (in press). “Illusions of normality”: A methodological critique of category-specific naming. *Cortex*. 516–517
- Laws, K. R., & Gale, T. M. (2002). Category-specific naming and the ‘visual’ characteristics of line drawn stimuli. *Cortex*, *38*, 7–21. 518–519
- Laws, K. R., Gale, T. M., Frank, R., & Davey, N. (2002). Visual similarity is greater for line drawings of nonliving than living things: The importance of musical instruments and body-parts. *Brain and Cognition*, *48*, 421–423. 520–523
- Laws, K. R., Gale, T. M., Leeson, V. C., & Crawford, J. (2005). When is category specific in Alzheimer’s disease? *Cortex*, *41*, 452–463. 524–525
- Laws, K. R., Leeson, V. C., & Gale, T. M. (2002). The effect of ‘masking’ on picture naming latencies. *Cortex*, *38*, 137–147. 526–527
- Laws, K. R., & Neve, C. A. (1999). ‘Normal’ category-specific advantage for naming living things. *Neuropsychologia*, *37*, 1263–1269. 528–529
- Lloyd-Jones, T., & Humphreys, G. W. (1997a). Perceptual differentiation as a source of category effects in object processing: Evidence from naming and object decision. *Memory and Cognition*, *25*, 18–35. 530–532
- Lloyd-Jones, T., & Humphreys, G. W. (1997b). Categorizing chairs and naming pears: category differences in object processing as a function of task and priming. *Memory and Cognition*, *25*, 606–624. 533–535
- McKenna, P., & Parry, R. (1994). Category-specificity in the naming of natural and man-made objects. *Neuropsychological Rehabilitation*, *4*, 255–281. 536–538
- Parkin, A. J., & Stewart, F. (1993). Category-specific impairments? No. A critique of Sartori et al. *Quarterly Journal of Experimental Psychology*, *46A*, 505–509. 539–541
- Price, C. J., & Humphreys, G. W. (1989). The effects of surface detail on object categorization and naming. *Quarterly Journal of Experimental Psychology*, *41A*, 797–828. 542–544
- Rossion, B., & Pourtois, G. (2004). Revisiting Snodgrass and Vanderwart’s object pictorial set: the role of surface detail in basic-level object recognition. *Perception*, *33*, 217–236. 545–547
- Snodgrass, J. G., & Vanderwart, M. (1980). A standardised set of 260 pictures: Norms for name agreement, image agreement, familiarity and visual complexity. *Journal of Experimental Psychology: Human Learning and Memory*, *6*, 174–215. 548–550
- Tranel, D., Logan, C. G., Frank, R. J., & Damasio, A. R. (1997). Explaining category-related effects in the retrieval of conceptual and lexical knowledge for concrete entities: Operationalisation and analysis of factors. *Neuropsychologia*, *35*, 1329–1339. 551–555

487 **References**

- 488 Barbarotto, R., Capitani, E., & Laiacona, M. (2001). Living musical instru-  
489 ments and inanimate body parts. *Neuropsychologia*, *39*, 406–414.